

उत्पाद मैन्युअल

जिंक सल्फेट मोनोहाइड्रेट, कृषि ग्रेड — विशिष्टि

IS 15848: 2025 के अनुसार PRODUCT MANUAL

Zinc Sulphate, Monohydrate, Agricultural Grade — Specification ACCORDING TO IS 15848: 2025

विभिन्न उत्पादों के लिए भारतीय मानक ब्यूरो) अनुरूपता मूल्यांकन (विनियम, 2018 की योजना -। के तहत प्रमाणन के संचालन में एकरूपता और पारदर्शिता के लिए इस उत्पाद मैनुअल का उपयोग सभी क्षेत्रीय / शाखा कार्यालयों और लाइसेंसधारियों द्वारा संदर्भ सामग्री के रूप में किया जाएगा। दस्तावेज़ का उपयोग बीआईएस प्रमाणन प्राप्त करने के इच्छुक संभावित आवेदकों द्वारा भी किया जा सकता है।

This Product Manual shall be used as reference material by all Regional/Branch Offices & licensees to ensure uniformity of practice and transparency in operation of certification under Scheme-I of Bureau of Indian Standards (Conformity Assessment) Regulations,2018 for various products. The document may also be used by prospective applicants desirous of obtaining BIS certification.

	T		10 10010				
1.	मानक संख्या	:	IS 15848 : 2025				
	IS No.						
	शीर्षक	:	Zinc Sulphate, Monohydrate, Agricultural Grade — Specification				
	Title		Specification				
	संशोधनों की संख्या	:	NIL				
	No. of amendments						
2.	नमूना दिशानिर्देश						
	Sampling Guidelines						
,	कच्चा माल		N1 - 17				
a)	Raw material	:	No specific requirements				
			Note: This section indicates the requirements for raw material (if specified in the IS) for which compliance is to be established during Grant of Licence/Change in Scope of Licence/Factory Surveillance.				
b)	समूहीकरण दिशानिर्देश Grouping Guidelines	:	NA				
c)	नमूने का परिमाण	:	500 g				
	Sample Quantity		Note: This section indicates the quantity of the sample of the product and/or the raw material (if applicable), required to be sent to the laboratory for testing, for the purpose of Grant of Licence/Change in Scope of Licence/Factory Surveillance (in case of market surveillance, effort may be made to procure the required quantity of product sample, as far as possible since raw material sample may not be available in market).				

d)	परीक्षण अनुरोध में घोषित	:	Name of the product				
	किए जाने वाले पैरामीटर						
	Parameters to be Declared in Test Request		Note: Apart from the above, any other requirements/parameters may also be declared as per the standard, as applicable.				
3.	परीक्षण उपकरणों की सूची	:	Please refer ANNEX-A				
	List of Test Equipment						
4.	निरीक्षण और परीक्षण की स्कीम	:	Please refer ANNEX-B				
	Scheme of Inspection						
	and Testing						
5.	एक दिन में संभावित परीक्षण						
	Possible tests in a day						
	All tests are possible to be carried out in a day.						
	Note: This section is for the guidance of BIS Certification Officers/Technical Auditors of BIS Authorized Outside Surveillance Agencies (OSAs) during factory inspection to provide ready reference regarding the tests which can be witnessed during the inspection in the factory by the officer/auditor.						
6.	लाइसेंस का दायरा/Scope of the Licence:						
	Licence is granted to use Standard Mark as per IS 15848: 2025 with the following scope:						
	Name of the product : Zinc Sulphate, Monohydrate, Agricultural Grade						

BUREAU OF INDIAN STANDARDS MANAK BHAVAN,9, BAHADUR SHAH ZAFAR MARG, NEW DELHI-110002

ANNEX-A

LIST OF TEST EQUIPMENTS

(INDICATIVE LIST, FOR GUIDANCE ONLY)

SI. No.	Tests used in with Clause Reference	Test Equipment/Chemical				
1.	Zinc, Clauses 3.2 & Table 1	Method I - Modified Ethylene Diamine Tetra				
		Acetate (EDTA):				
		Disodium Ethylene Diamine Tetra Acetate (EDTA), Discillatory.				
		- Distilled Water				
		Zinc Metal Analytical Reagent Grade				
		Ammonium Hydroxide,Ammonium Chloride,				
		Animonium Chloride,Sodium Cyndie,				
		Sodium Cylidie,Sodium Chloride,				
		Sodium Chloride,Eriochrome Black Indicator,				
		Formaldehyde				
		- Glacial Acetic Acid				
		 Hydroxylamine Hydrochloride-AR Grade, 				
		Hydroxyl chloride AR Grade				
		Method II - Absorption Spectrophotometric Method				
ĺ		 Standard Zinc Solution, 				
		- Glass Distilled or Demineralized Water of pH 2.5±				
		0.5,				
		Atomic Absorption Spectrophotometer at a				
2.	Magnesium (as Mg), Clauses 3.2	wavelength of 213.8 nm. Method I- EDTA Method:				
۷.	& Table 1					
	& Table 1	- Dilute Sulphuric Acid				
		- Dilute Nitric Acid				
		- Sodium Sulphide Solution				
		Eriochrome Black T Indicator Bridge Street T Indicator				
		Diammonium Hydrogen Phosphate				
		Ammonium Hydroxide - Ammonium Chloride				
		Buffer Solution				
		 Standard Magnesium Solution-0.01 M 				
		 Ethylene Diamine Tetra Acetate (EDTA) 				
		Solution				
		 Analytical balance 				
		 Standard glassware 				
		Method II - Atomic Absorption Method:				
		Strontium Chloride				
		 Standard Magnesium Solution 				
		 Atomic Absorption Spectrophotometer 				
		wavelength of 285.5 nm.				

3.	Copper, Clauses 3.2 & Table 1	 Method I - Diethyl Dithiocarbonate Method: Strontium Chloride Standard Magnesium Solution Standard glassware Method II - (Atomic Absorption Method): Standard Copper Solution, Glass Distilled or Mineralized Acidified water pH 2.5 +0.5, Atomic Absorption Spectrophotometer wavelength of 285.5 nm.
4.	Lead, Clauses 3.2 & Table 1	Method I - Dithiozone Method: - Strontium Chloride - Standard Magnesium Solution - Dilute Nitric acid - Standard glassware.
		Method II - Atomic Absorption Method: - Standard Lead Solution - Nitric Acid Solution 1 Percent - Zinc Sulphate Solution 20 Percent - Analytical balance - Standard glassware
5.	pH, Clauses 3.2 & Table 1	Arrangement for boiling waterpH meter.
6.	Matter Insoluble in water, Clauses 3.2 & Table 1	 Dilute Sulphuric Acid 10 percent Weighing balance Gooch crucible or sintered glass crucible (G No. 4) Hot air oven-capable of operating at (110 ± 5) °C
7.	Iron, Clauses 3.2 & Table 1	Method I - Spectrophotometric Method - Photoelectric –colorimeter - Bromophenol Blue Indicator - Sodium Citrate Solution 25% - Hydroquinone Solution 1 % - Ortho -phenanthroline Solution 0 .25 % - Dilute Hydrochloric Acid - Standard Iron Solution, Heating mental - Whatman filter paper No. 40 Method II - Atomic Absorption Method: - Standard Iron Solution (1000 ppm) - Glass Distillated or Demineralized Water of pH-2.5+ 0.5

		Atomic Absorption Spectrophotometer wavelength of 248.3 nm.
8.	Sulphur, Clauses 3.2 & Table 1	Gravimetric Method: - Barium chloride - Bromine - Grahan tetrachleride (Respect Grade)
		 Carbon tetrachloride (Reagent Grade) Whatman filter paper No. 42 Beaker-250ml Concentrated nitric acid
		 Hot plate/Water bath. Concentrated hydrochloric acid Hot water Kjeldahl flask
		 70 to 72 percent perchloric acid Carbon disulphide Gooch crucible 1% silver nitrate solution
		 Furnace Desiccator Turbidity Method: Sodium chloride
		 Hydrochloric acid Glycerol-alcohol Solution Dry (Analytical Reagent Grade) potassium sulphate Distilled water
		 (Analytical Reagent Grade) sodium chloride Concentrated hydrochloric acid Barium chloride - Use crystals of (Analytical Reagent Grade) barium chloride that pass through a
		20-mesh sieve and are retained by a 30-mesh sieve - Pure glycerol - Absolute ethanol - Burette
		 100 ml volumetric flasks Stoppers EEL nephelometer Galvanometer
		 Whatman No. 40 filter paper Silica basin Silica clock glass Cool silica-lined muffle furnace
		Water-bathHot-plateNitric Acid

9.	Cadmium, Clauses 3.2 & Table 1	_	Pure cadmium metal
		_	250 ml beaker
		_	Concentrated nitric acid
		_	One litre flask
		_	Distilled water
		_	sulphuric acid or sodium hydroxide solution
		_	Atomic absorption spectrophotometer
		_	Air Acetylene flame
10.	Arsenic, Clauses 3.2 & Table 1	_	Concentrated Hydrochloric Acid — AR grade
		_	0.5 M HCl
		_	Potassium Iodide Solution C (2.5%)
		_	10 % Stannous Chloride Solution
		_	0.75 Percent Stannous Chloride Solution
		_	6 Ethyl Alcohol (Absolute) — 95 %
		_	Mercuric Chloride Solution
		_	Filter Paper (Whatman No. 40) — nine cm diameter
			or comparable grade
		_	Mercuric Chloride Paper
		_	Lead Acetate Solution
		_	Glass Wool
		_	Zinc Pellets (Arsenic Free Zinc Pellets) — AR
			grade
		_	Sodium Arsenate (Na2HAsO4.7H2O)
		_	Distilled water
		_	Volumetric flasks
		_	Concentrated hydrochloric acid
		_	Gutzeit bottle

ANNEX-B

SCHEME OF INSPECTION AND TESTING

1. QUALITY ASSURANCE PLAN

- 1.1 It is expected that manufacturers (licensees/applicants) will implement a Quality Assurance Plan i.e. a plan of regular testing and in-process controls, designed to ensure that the product bearing the Standard Mark conforms to all requirements of the Indian Standard.
- 1.2 The manufacturers shall define a Quality Assurance Plan defining the control unit (i.e. lot/batch etc.) and the levels of control (i.e. the frequency and number of samples for conducting the different tests as per the Indian Standard) and submit the same to BIS Branch Office for information. The manufacturer shall comply with the same and maintain test records in accordance with para 2.4.

1.3 RECOMMENDED LEVELS OF CONTROL/CONTROL UNIT:

- 1.3.1 For the guidance of manufacturers, the recommended definition of control unit is: the quantity of the zinc sulphate, monohydrate, agricultural grade produced using same raw material & under similar conditions of manufacturing in a day.
- 1.3.2 For the guidance of manufacturers in preparing the Quality Assurance Plan, recommended levels of control are given in **Table 1**.
- 1.3.3 The manufacturer shall ensure inspection and testing as per the Quality Assurance Plan submitted by them on the whole production of the factory which is covered by this plan. Alternatively, the manufacturer has the option of adherence to the quality plan as per levels of control recommended in column 3 of Table 1.
- 1.4 However, all manufacturers shall ensure compliance of their products to all the requirements of the Indian Standard.
- 2. ENSURING COMPLIANCE THROUGH TESTING- It is expected that manufacturers (licensees/applicants) will establish a suitably equipped and staffed in house laboratory (In house testing facility) for testing at least those parameters of the Indian Standard which require routine testing for ensuring quality of the product. This includes in-process controls as may be defined and put in place by the manufacturer and testing parameters/requirements which can only be performed in the factory.
- 2.1 For the guidance of manufacturers, Table 1 giving the recommended levels of control is given below. Column 2 of Table 1 indicates routine tests where test equipment is required in house as "R" or other tests which can be subcontracted as "S". Subcontracting is permitted to BIS recognized/empanelled laboratory or any other laboratory having valid NABL accreditation as per IS/ISO/IEC 17025.
- 2.2 For MSME manufacturers, the requirement of maintaining a laboratory/in-house testing facility for routine tests (indicated as "R" in Column 2 of Table 1) is also optional.
- 2.2.1 MSME manufacturers may utilize common cluster based facilities as per guidelines for the utilization of cluster based test facilities by MSMEs or the provisions of Sharing of testing facilities or get testing done from BIS recognized/empaneled laboratory or any other laboratory having valid NABL accreditation as per IS/ISO/IEC 17025.

- 2.3 Large Scale manufacturers shall maintain an in-house laboratory equipped at least with test facilities for routine tests (indicated as "R" in Column 2 of Table 1), where different tests given in the specification shall be carried out in accordance with the method given in the specification. They shall also implement a calibration plan for the in-house test equipment.
- 2.3.1 Alternatively, in lieu of an in-house laboratory, large scale manufacturers can also utilize the provisions of Sharing of testing facilities as per the Guidelines for Grant of Licence available on BIS website www.bis.gov.in. (Under Conformity Assessment>Product Certification Process). Even for subcontracted tests, provisions for sharing of testing facilities can be utilized.
- 2.4 **TEST RECORDS** The manufacturers maintaining an in-house laboratory or utilizing common cluster based facilities or shared test facilities shall maintain test records for the tests carried out to establish conformity. For the tests being subcontracted to BIS recognized/empanelled laboratory or any other laboratory having valid NABL accreditation as per IS/ISO/IEC 17025, test reports issued by the laboratories shall be available for inspection by BIS.
- **3. PACKING AND MARKING** The Standard Mark as given in the Schedule of the licence shall be incorporated legibly and indelibly on each bag of zinc sulphate, monohydrate, agricultural grade provided always that the material so marked conforms to each requirement of the specification.
- 3.1 Packing and Marking shall be done as per the Indian Standard.
- 3.2 **Additional Marking requirements**: The material shall also be marked with the following additional requirement on each bag of zinc sulphate, monohydrate, agricultural grade:
- a) "For BIS certification details please visit www.bis.gov.in"
- **4. REJECTION -** All the production which conforms to the Indian Standard and covered under the scope of this licence shall be marked with the Standard Mark. Disposal of non-conforming product shall be done in such a way so as to ensure that there is no violation of provisions of BIS Act, 2016.

TABLE 1 (ONLY FOR GUIDANCE PURPOSE)

(1) TEST DETAILS				(2)	(3)		
				Test equipment requirement	LEVELS OF CONTROL		
Clause	Requirement	Test Methods		R: required (or)	No. of Sample	Frequency	Remarks
		Clause	Reference	S: Sub-contracting permitted			
3.1	Description	3.1	IS 15848	R	One	Each control Unit	
3.2 & Table 1 (i)	Zinc (as Zn), Percent by mass	Annex A	IS 15848	R	One	Each control Unit	
(ii)	Magnesium (as Mg), Percent by mass	Annex B	IS 15848	R	One	Each control Unit	
(iii)	Copper (as Cu), Percent by mass	Annex C	IS 15848	R	One	Each control Unit	
(iv)	Lead (as Pb), Percent by mass	Annex D	IS 15848	R	One	Each control Unit	
(v)	pH of 5 percent solution	Annex E	IS 15848	R	One	Each control Unit	
(vi)	Matter insoluble in water, Percent by mass	Annex F	IS 15848	R	One	Each control Unit	
(vii)	Iron (as Fe), Percent by mass	Annex G	IS 15848	R	One	Each control Unit	
(viii)	Sulphur (as S), percent by mass,		IS 6092 (Part 5)	R	One	Each control Unit	
(ix)	Cadmium (as Cd), percent by mass	Annex H	IS 15848	R	One	Each control Unit	
(x)	Arsenic (as As2O3), percent by mass	Annex J	IS 15848	R	One	Each control Unit	